

VALMEX® FR 580

Lightweight – strong – versatile

VALMEX® FR 580 is a high-value technical textile for various applications, primarily for permanent and temporary tensioned structures, tents and sun shading. It has been developed by Mehler Technologies to provide architects, engineers and manufacturers with a coated fabric displaying similar characteristics as the premium VALMEX® MEHATOP F quality range on short-span shaped tensile architecture creations.

The weight of 580 gr/sqm enables applications that require very light as well as robust fabrics. VALMEX® FR 580S is a PVC coated Polyester low-wick base fabric, finished with PVDF lacquer on its top side. It is treated fungicide and UV stabilized. The flame retardancy has been verified by the major fire tests like DIN 4102: B1, NFP 92507: M2 and D.M. 26.06.84 (UNI 9177): CL. 1.

VALMEX® FR 580

Coating	PVC
Finish	PVDF lacquer on top side, fungicide, low-wick
Weight	580 g/m²
Tensile strength (warp/weft)	2900/2700 N/50mm
Tear strength (warp/weft)	300/300 N
Adhesion	16 N/cm
Cold resistance	-30 °C
Heat resistance	+70 °C
Light fastness	>6 Note
Crack resistance	@100000 x
Width	250 cm

Different widths and several colours available on request




Our commitment to
environmental responsibility
and sustainability



distributed by

SHANN



Melbourne	03 8480 0800
Sydney	02 9832 7000
Brisbane	07 3808 7277
Gold Coast	07 5593 8288
Adelaide	08 8277 7733
Perth	08 9244 4433
Darwin	0413 366 750
Auckland	09 820 0780

www.shann.com.au


VALMEX® FR 580S



958* bright white




907* white RAL 9010



141* pearl white RAL 1013




112* nature




184* pampa




114 brilliant yellow




356 flame red RAL 3000



371 burgund red



542 blue



636 dutch green



724 bright grey



905 black

* low-wick

Our commitment to
environmental responsibility
and sustainability



V244(07/2011